

NK TRACKED SLIDING GATE



NK TRACKED GATES

GENERAL SPECIFICATIONS

Tracked sliding gate leafs, framework construction comprising of a welded SHS structure with a range of infill options.

INFILL: Mesh panel cladding to suit adjacent fence line.

AVAILABLE HEIGHTS: 1.8m, 2.0m, and 2.4m.

AVAILABLE WIDTHS: 3.0m to 8.0m (ranging in 1m increments).

OPERATION TIME: 4 seconds / m (variable).

POWER UNIT: Single phase 650W motor.

STANDARD CONTROL: 1 Nr deadmans keyswitch to inside of cabinet (Hold to run function).

KEY FEATURES: The NK Tracked sliding gate guarantees smooth, consistent and quiet gate movement, as a result of the tried and tested external rack & wheel drive mechanism.

A securely concealed manual release mechanism is included as standard allowing manual control of the gate in the event of a power failure.

The NK Tracked sliding gate is fully compliant with BS/EN 12453 safety features in accordance with European Standards and Regulations.

ADDITIONAL ITEMS: Control Options: Stainless steel Intercom, Stainless steel Videocom, Stainless steel key pad, Stand alone prox reader, Network prox reader and additional Hand held radio Transmitters. Safety Options: Safety edges, Photocells, Flashing Light & beacon.

*All dimensions represent nominal values.

For further details on our complete automation range along with technical specifications, please visit our website at:

www.nkfencing.com

RELATED PRODUCTS

OTHER PRODUCTS:

- ▶ NK Swinging Gates
- ▶ NK 9000 Auto Sliding Gates
- ▶ NK Traffic Barriers
- ▶ NK 9100 Auto Sliding Gates
- ▶ NK Swinging Barriers
- ▶ NK Bollards

NK FENCING - Access control made simple

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.



BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019