



GENERAL SPECIFICATIONS

INSTALLATION: Fencing is erected in accordance with a unique site installation plan, ensuring straight fence lines or smoothly flowing curves, with top of posts following profile of the ground, set rigid and plumb to retain perimeter integrity.

POST SYSTEM: RHS at 2.525m centres, panel fixed to posts with 40 x 5mm slotted clamp bar and M8 stainless steel anti-vandal fittings.

PANEL WIDTH: 2.5m.

MESH APERTURE: 200mm x 50mm.

WIRE DIAMETER: 8mm twin horizontal, 6mm vertical.

FINISH: Galvanised or galvanised and powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION RHS	NUMBER OF FIXINGS	FIXING TYPE
2.00	60x40	6	M8 stainless steel anti-vandal screws
2.40	80x40	7	M8 stainless steel anti-vandal screws
3.00	80x40	9	M8 stainless steel anti-vandal screws

* All dimensions represent nominal values.

KEY FEATURES: The ultimate deterrent, providing the highest degree of physical perimeter protection with an open mesh pattern allowing high visibility, resulting in a police approved fencing system which is difficult to penetrate or scale.

POLICE APPROVED SPECIFICATION



CERTIFICATION STANDARD: This fencing system complies with the requirements of LPS 1175: "Secured by Design" and is certified by the Loss Prevention Certification Board (LPCB).

GATES: NK Automated Cantilever Sliding Gates are also available to compliment your access control solution.

OTHER PRODUCTS:

- ▶ Ibex High Security
- ▶ NK Ibex Elite
- ▶ NK Ibex Supreme 656
- ▶ Ibex Security
- ▶ Ibex Supreme 868
- ▶ Ibex Premier Plus

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.



BLACK RAL 9005 GREY RAL 7037 BLUE RAL 5010 WHITE RAL 9010 GREEN RAL 6005 RED RAL 3000 YELLOW RAL 1006 BROWN RAL 8019