



NK IBEX

GENERAL SPECIFICATIONS

POST SYSTEM: RHS at 3.025m centres, panel fixed to posts with NK clip type 008 using NK M8 tamper-resistant bolts and hexagonal anti-rotational threaded nutserts.

PANEL WIDTH: 3m

MESH APERTURE: 150 x 50mm with Safetop fold top & bottom

WIRE DIAMETER: 5mm horizontal, 5mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION	NUMBER OF FIXINGS
0.9	60x60	3
1.20	60x60	4
1.50	60x60	4
1.80	60x60	4

APPLICATION: NK IbeX Safetop is a general purpose fencing system for boundary demarcation and aesthetic perimeters. Widely used in the commercial and public construction sectors by building contractors, and especially suited to parks, playgrounds and schools due to its low impalement risk design.

* All dimensions represent nominal values.

KEY FEATURES: NK IbeX Safetop is constructed from folded rigid mesh panels with 5mm horizontal and 5mm vertical wires, securely fixed to posts at multiple points using NK clip type 008 & NK M8 tamper-resistant bolts. All panels have Safetop folds top and bottom, which eliminates impalement risks from short wire protrusions. Installation of all fencing is subject to site specific risk assessments and NK recommends due regard should be given to nearby aids to scaling or natural overhangs.

OPTIONAL EXTRAS: NK IbeX Safetop slotted clampbar fixings.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or with automated control.

OTHER PRODUCTS:

- ▶ NK IbeX Vogue
- ▶ NK IbeX Premier Plus
- ▶ NK IbeX Elite
- ▶ NK Playground Railings
- ▶ NK IbeX Supreme 868

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019