



NK CRASH BARRIER

GENERAL SPECIFICATIONS

DESCRIPTION: A mild steel cold formed W section crash barrier designed for vehicle crash mitigation in an off road setting. This untensioned system consists of steel posts and W section corrugated steel beams.

HEIGHT: 0.61m, 0.76m & 1.1m.

POST DETAIL: 127 x 76 UB Grade 2 S275JR or 100 x 50 x 5mm Z post 1.2m long set at 3.2m centres.

BEAM DETAIL: Mild steel 3mm thk cold formed W section corrugated beam. 3.2m effective length, 3.504m overall length.

FIXING DETAIL: Panels fixed together with 8 No M16x35 Hex bolts, nuts and washers. Panels fixed to posts with 1 No M16x50 hex bolt, nut and washers.

FINISH: Galvanised to BS EN 1461-2009.

APPLICATION: Off road vehicle crash mitigation barrier and / or roadway demarcation. Suitability of product and performance following installation is dependent on specific site conditions.

*All dimensions represent nominal values.

KEY FEATURES: Accessories include Fish tail end, Pedestrian end, Yellow PVC barrier end sleeve, 90 degree corners, 135 degree corners, flexible corners and yellow PVC post caps. Base plated alternative setting is available on request.

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK Acoustic Barrier - Type A
- ▶ NK Acoustic Barrier - Type R
- ▶ NK On Road Guardrail
- ▶ NK Standard Guardrail
- ▶ NK NRA Spec Guardrail
- ▶ NK Anti-Vandal Options

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019